

Fine Line Tape Olive

Description

Bodyline Fine Line Tape Olive uses a thermally stabilized polypropylene backing with a urethane based pressure sensitive adhesive. This fine line tape will perform in temperatures up to 138°C for at least 45 minutes and leave a sharp, clean separation line. It adheres to a wide variety of surfaces. It follows contours and remains in place as long as necessary and leaves no residue upon removal. Bodyline Fine Line Tape Olive meets military specification T-215955D type III.

Recommended Uses

Preferred where tape must conform and follow contours without wrinkling or tearing. Bodyline Fine Line Tape Olive is used when flake resistance and removal without adhesive transfer is important.

Product Construction



Shelf Life

One year from date of receipt by customer when stored at 22°C (72°F) and 50% relative humidity.

Physical Properties

Values shown are typical values not to be used for specification purposes.

Carrier	Embossed Polypropylene
Colour	Olive Green
Adhesive	Pigmented Urethane Pressure Sensitive Adhesive
Thickness	0.127mm PSTC-33
Width	3mm, 6mm, 9mm, 12mm (+/- 1mm)
Length	55m (+/- 0.1m)

Performance Properties

Values shown are typical values not to be used for specification purposes.

Tensile Strength	0.215 kg/mm ASTM D-3759
Elongation Strength	600 %
Adhesion to Steel	33.6 g/mm ASTM D-3330
Heat Resistance	138°C Maximum for 45 minutes

The information contained in this sheet represents our current data and best opinion as to the proper use in handling of this product under normal conditions. Any other use or process is the responsibility of the user.

FOR PROFESSIONAL USE ONLY