

Tar & Glue Remover

Description

Contains: Distillate, Xylene

A powerful solvent that rapidly removes residues of most types of adhesives and sealants used in the motor industry. Formulated to have the minimum effect on paint work and upholstery materials. A most effective tar remover for wheels and bodywork.

Directions

Apply with a clean soft cloth and rub gently until the residue is removed. To confirm that a particular surface is suitable for cleaning with this product, test a small, hidden area before use. Avoid over application and soaking, which may soften some materials.

Please refer to product safety data sheet before use. Use only as directed.

Health & Safety

Classification



HARMFUL (Contains Xylene)

Risk phrases

- R10 Flammable.
- R20/21 Harmful by inhalation and in contact with skin.
- R38 Irritating to skin.
- R43 May cause sensitisation by skin contact.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.

Safety phrases

- S36/37 Wear suitable protective clothing and gloves.
- S51 Use only in well ventilated area
- S60 This material and its container must be disposed of as hazardous waste.
- S61 Avoid release to the environment. Refer to special instructions/safety data sheets.
- S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

The information contained in this sheet represents our current data and best opinion as to the proper use in handling of this product under normal conditions. Any other use or process is the responsibility of the user.

FOR PROFESSIONAL USE ONLY