



Rub Through Etch Primer Aerosol

February 2025

Product Code:	BDPBRTPA
Revision Date:	18.02.2025
Revision Number:	01
Company:	PPG Industries (UK) Limited
Address:	Needham Road, Stowmarket, Suffolk IP14 2AD U.K.
Telephone:	0044 (0) 1449 773338

Part Numbers:

Part No.	Description
BDPBRTPA	Rub Through Etch Primer Aerosol

Description: The Bodyline rub-through primer gives the ultimate adhesion onto many difficult substrates including alloy, stainless steel, zintec and galvanise. It comes supplied with two nozzles – 1 variable nozzle and 1 standard round nozzle.

Suitable Substrates: Bare steel • Cured paintings • Polyester substrates • Aluminium and galvanised sheet metals

Physical Properties:

Basis of binder	Nitro Cellulose
Colour	Grey
Coverage	1.25m ²
Temperature resistance	to 90°C
Storage stability	10 years in appropriate storage (-10°-25°C, relative air humidity of max. 60%)
Size	500ml
VOC Content	338 g/500ml

Envinromental: This product is 100% free of heavy metals and the caps and packaging are made of recyclable material.

Directions for use:



	Shake aerosol for at least two minutes, after agitator ball is free		3 Minutes
	Apply in cross coats from distance of 250mm from object		20 minutes @ 20°C
	1-2 coats @ 10 - 20µm		After use, turn aerosol upside down and empty valve
	10 - 15 minutes @ 20°C		

This data sheet is compiled to be of assistance but without guarantee. Users are responsible for safe working practices and PPE requirements. Final determination of suitability of any material is the sole responsibility of the user. For profesional use only.

